


Supplies

- 2 yards 36-inch-wide muslin
- 2 yards, or more, 36-inch-wide lace, scalloped on both selvages
- 2 yards lining (Use silky fabric for a drapey skirt or cotton for a structured look.)
- 2 packages narrow, double-fold binding
- 3 yards 1-inch-wide satin ribbon

Make the skirt pattern


Drape the muslin to make a skirt pattern. This goes faster with a friend's help, so see if you can enlist someone to help you wrap and measure. Wear leggings you can pin into for the draping process. If you have a dress form that reflects your shape accurately, follow these steps to drape the skirt on it instead of your body.



◀ WRAP THE MUSLIN AROUND YOUR HIPS. With the selvage at waist level and parallel to the floor, place the muslin's vertical edge along the line where a right side seam would sit on your body. Pin the muslin in place carefully at the level of your widest hip circumference. Wrap the muslin loosely across your abdomen. Keep the selvages parallel to the floor. Pin the muslin at the side seam location on your left hip. Wrap the muslin around your back and pin again on your right hip (just above the first pin).

TINCH OUT THE SKIRT DARTS. With a friend's help, fold out the excess waist fabric into four darts from waist to hip: one at each side, and two symmetrical darts about halfway between the sides and center back. Pin through the folds, close to the body. Adjust the folds until the waistline fits and the skirt falls to your hips without puckering. Trace the crease on both sides of each fold.

TREMOVE THE MUSLIN, AND COMPLETE THE SKIRT PATTERN. Trim the muslin at the hemline mark, parallel to the selvage and the waistline. Shape the overlay and the underlay corners into matching curves with a fashion ruler. If you don't have a fashion ruler, try tracing the edge of a large round platter or pizza pan.



is in floral-printed lace from MoodFabrics.com.


ace is easy to sew and in the height of

fashion. This wrap skirt project has no side seams, simplifying and speeding


Construct the skirt

First cut the lining and lace, using the muslin as the pattern. These instructions use binding to edge the lining, so it does not require a hem allowance. The pattern also doesn't include side seams, so the construction phase is swift.

Cut the layers



TRACE THE LACE
DARTS. The lace hangs
slightly below the lining
on the finished skirt, so
align the muslin on the
lace with a scalloped
selvage ½ inch to 1 inch
beyond the muslin's hem
edge. Cut the lining along
the muslin's edge. Mark
the darts on it with a airsoluble fabric marker.



2 CUT THE LACE OVERLAY EDGING.

TEST YOUR LACE

Test-sew your lace to see if it requires a

stabilizer. If the lace is very open and/or

soft and pulls down into the needle plate, try Stitch & Ditch Stabilizer by ThreadPro.


It comes in 3-inch-wide rolls. Just place a

length between the lace and the feed dogs, stitch, and tear away the stabilizer later.


The lace overlay's curved edge is trimmed with appliquéd scalloped selvage cut from the opposite selvage on the lace yardage. Cut a generous length and width—you can trim the edging after matching the motifs and stitching it in place.

Sew the lining

FOLD THE LINING DARTS RIGHT SIDES TOGETHER.
Sew the darts, stitching from the waistline to the points. Press the darts toward center back.




2 BIND THE LINING'S HEM AND CURVED EDGES. The double-fold binding has one side that is slightly narrower; open the binding along this fold. With right sides together and starting at the waistline, align the binding's raw edge to the lining's. With the binding on top, stitch in the fold.




PHOTOS: SLOAN HOWARD, STYLIST: JESSICA SAAL. ILLUSTRATIONS; EMILY BRONSON. STY (P. 28) TOP—(MADEWELLCOM); (P. 31) TOP—(MADEWELLCOM), SWEATER—(TARGETCON AND CLASSES—(ANTHROPOLOGIE-COM), SHOFS—STRYE MADDEN (MACYS, COM)

Sew the lace





LAP AND SEW THE DARTS IN THE LACE.
Cut the lace darts at center, from the waistline to the point. With the top layer moving toward center back, overlap the dart sides until the thread tracings align. Stitch each lapped dart from waistline to point with a narrow zigzag. Use stabilizer to manage the lace, if necessary. Trim the excess lace, and remove the thread tracings. Staystitch ½ inch from the waistline.




2 CAREFULLY ALIGN AND TRIM THE SCALLOPED LACE SELVAGE TO FIT THE OVERLAY'S EDGE. Use a narrow zigzag to stitch the trim to the overlay's edge, keeping the motif matched and intact as much as possible.

Put the skirt layers together





LAYER THE LINING AND THE LACE RIGHT SIDES TOGETHER. Align the layers at the waistline. The lace layer should be slightly longer at the hem and overlay edges. Pin, then stitch together with a ½-inch seam allowance (A). Flip the lace and lining right sides out. Press along the waistline seam (B).



2 STITCH THE WAISTBAND RIBBON TO THE SKIRT. Leave a yard of ribbon loose (to tie), then align the ribbon just within to the waistline seam/edge on the overlay's right side. Stitch through the ribbon and skirt very close to the edge. Stop stitching at the left side dart. Don't cut the ribbon, but pivot with the needle down and stitch back to the overlay edge, along the ribbon's other edge. Tie and trim the ribbon ends.

3 ADD A BUTTON OR SNAP. Place it at the right side of the waistband to connect the underlay and overlay. For security, add a snap at the right side, too, beneath the overlay where it is tied to the skirt back.



Highlight a delicate lace with contrast lining.

30 sewstylish ■ SewStylish.com WINTER 2012 31